

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>B05D 5/06, B41J 2/41, G03G 15/10</b>		<b>A1</b>	(11) International Publication Number: <b>WO 00/21690</b>
			(43) International Publication Date: 20 April 2000 (20.04.00)
(21) International Application Number: PCT/US99/23612		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 12 October 1999 (12.10.99)			
(30) Priority Data: 60/104,079 13 October 1998 (13.10.98) US			
(71) Applicant (for all designated States except US): ELECTROX CORPORATION [US/US]; Suite 124, 400 Morris Avenue, Denville, NJ 07834 (US).			
(72) Inventor; and (75) Inventor/Applicant (for US only): DETIG, Robert, H. [US/US]; 80 Deep Dale Drive, Berkeley Heights, NJ 07922 (US).			
(74) Agent: WOODBRIDGE, Richard, C.; Woodbridge & Associates, P.C., P.O. Box 592, Princeton, NJ 08542 (US).			
(54) Title: ELECTROSTATIC PRINTING OF FUNCTIONAL TONER MATERIALS FOR ELECTRONIC MANUFACTURING APPLICATIONS			

## (57) Abstract

The invention describes techniques for the electrostatic printing of functional materials configured as liquid toners (50) on glass substrates (26) in a non-contact mode. The toners are patterned by a sensitized electrostatic printing plate (11) of fixed image configuration. Toner images (50) are transferred by an electric field (33) across a fluid filled mechanical gap (42) to the glass substrate (26). Techniques for optimizing the imaging and transfer processes are also disclosed. Two other techniques in which partially finished pieces are manipulated to "self-print" themselves, are described. In both cases defects in the pieces will over print the defect in the "self-healing" mode.

